

# MT932 *easy*



## TECHNICAL DATA SHEET

- **Compact dimensions**  
l 4.70 m x w 2.34 m x h 2.30 m
- **Max. lifting height : 9.00 m**  
**Max. capacity : 3.2 T**
- **Optimized engine**  
Engine Stage 3B without particulate filter



**Easy to use**



**Easy to maintain**



**Easy to transport**



MT 932	
<b>Lifting</b>	
Max. capacity.	3200 kg
Max. lifting height.	9 m
Max. outreach	6.35 m
Break-out force with bucket (ISO 8313)	5770 daN
<b>Time unladen</b>	
Lifting	8.0 s
Lowering	5.5 s
Extension	13.3 s
Retraction	8.3 s
Crowd	3 s
Dump	2.9 s
<b>Tyres</b>	400/80-24
<b>Braking</b>	
Service brake	oil immersed multi-disc braking on front/rear axles
Parking brake	oil immersed multi-disc mechanics on the front axle
<b>Engine</b>	
DEUTZ - STAGE 3B-Final Tier IV	
Type	TD 3.6 L
cubic capacity	3621 cm <sup>3</sup>
Power	75 cv/55.4 kW
Max. torque	330 Nm
Injection	electronic
Cooling	water
Laden drawbar pull	7320 daN
<b>Transmission</b>	
torque converter	
Reversing shift	electrohydraulic control
Number of gears (forward/reverse)	4/4
Max. travel speed (may vary according to applicable regulations)	25 kph
Steering mode	4 wheel steer - 3 steering modes
<b>Controls</b>	
JSM® Joystick multi-function load limiter cut off system - EN15000 Norm	
<b>Hydraulics</b>	
Pump	gear type with priority valve 104 l/min - 260 bar
<b>Capacities</b>	
Hydraulic oil	128 l
Fuel	120 l
<b>Unladen weight (with forks)</b>	7145 kg
<b>Dimensions</b>	
<b>C.</b> Front wheel centre to carriage	1.13 m
<b>B.</b> Wheelbase	2.81 m
<b>I.</b> Rear wheel centre to rear face	0.76 m
<b>D.</b> Overall length to carriage	4.70 m
<b>G1.</b> Ground clearance	0.45 m
<b>J.</b> Overall width of cab	0.80 m
<b>F.</b> Inside tyre width	1.93 m
<b>W.</b> Overall width	2.34 m
<b>U1.</b> Overall height	2.30 m
Standard forks (length x width x thickness)	1200 x 125 x 45 mm
Turning radius (over tyres)	3.80m
Carriage rotation (crowd/dump)	13° / 113.8°
<b>Noise and vibration</b>	
Noise at driving position (LpA)	78 dB
Environmental noise (LwA)	104 dB
Vibration to whole hand/arm	<2.50 m/s <sup>2</sup>

mm	
<b>A</b>	1200
<b>B</b>	2810
<b>C</b>	1128
<b>C1</b>	1064
<b>D</b>	4696
<b>D1</b>	4632
<b>D2</b>	4193
<b>E</b>	5896
<b>F</b>	1930
<b>G</b>	450
<b>G1</b>	435
<b>G2</b>	435
<b>I</b>	758
<b>J</b>	890
<b>K</b>	1260
<b>L</b>	45
<b>N</b>	1715
<b>O</b>	125
<b>P2</b>	38°
<b>P3</b>	53°
<b>R</b>	3598
<b>S</b>	7533
<b>T</b>	3460
<b>U1</b>	2299
<b>U2</b>	2488
<b>V</b>	4770
<b>V1</b>	1310
<b>V2</b>	3800
<b>W</b>	2340
<b>Y</b>	13°
<b>Z</b>	113.8°

## Rough Terrain Load Chart

standard EN1459 B

### Machine on tyres with forks

