

TruckMaster®

PORTABLE DIESEL DISPENSING TANK WITH FUEL DISTRIBUTOR

- TruckMaster® is ideal for the refueling of heavy equipment at the site of use (tractors, trucks, combines, etc.).
- The TruckMaster® increases efficiency by removing the need to bring equipment to service stations for refuelling.
- An integrated partition inside the tank reduces the sloshing of fuel during transportation. Fuel transported without the partition could cause the tank, or even the car, to flip over.
- The TruckMaster® 430 and 900 litres has been tested to meet the requirements of the European Agreement (ADR) concerning the International Carriage of Dangerous Goods by Road, TruckMaster® 430l certificate no. 413/0/575 and TruckMaster® 900l certificate no. 448/0/1237.

STANDARD EQUIPMENT

Capacity	200 l	430 l	900 l
Level gauge inside the tank.		●	●
Increased flow rate- suction hose 1" with shut-off valve and mesh filter.	●	●	●
12V pump with max flow of 40 l/min.	●	●	●
6m power cable with holder.	●	●	●
4m flexible delivery hose.	●	●	●
Auto nozzle with holder.	●	●	●
Inlet with cup.	●	●	●
Spill-safe vent.	●	●	●
Lockable lid.**	●	●	●

AVAILABLE CAPACITIES AND DIMENSIONS



PRODUCT CODE
OTM00200DG/**

Capacity 200 l
Length 1.18 m
Width 0.86 m
Height 0.50 m



PRODUCT CODE
OTM00430DG/**

Capacity 430 l
Length 1.18 m
Width 0.86 m
Height 0.91 m



PRODUCT CODE
OTM00900DG/**

Capacity 900 l
Length 1.41 m
Width 1.05 m
Height 1.21 m

Product dimensions may vary within +/- 1%.
*** Code ending depends on product equipment.

OPTIONAL EQUIPMENT

Capacity	200 l	430 l	900 l
24V DC pump with max flow 43l/min.*		●	●
24/12 V DC pump with max flow 70/35l/min.*		●	●
Pump 12V or 24 V DC max flow 85l/min.*		●	●
230 V AC pump with max flow 56l/min.*		●	●
Digital flow meter with max precision of +/- 1%, placed close to the nozzle.		●	●
Digital flow meter with max precision of +/- 1% connected on pump outlet.		●	●
Manual delivery nozzle.	●		
4 side metal catches for safe TruckMaster® lifting.	●	●	●
Internal light- to ensure product use when dark.	●	●	●


Max capacity usable capacity 95% max volume.

* Attention! These values are the maximum flow rates provided by pump manufacturer. The actual flow is lower and it depends on the configuration of the suction device, the quality of its maintenance, oil parameters and temperature.

** TruckMaster® 900l is equipped with a gas strut supported lid.


TruckMaster® warranty: 5 years for tank leakproofness and 2 years for equipment.

The warranty applies to the product used in a manner consistent with manufacturer's recommendations.




TRANSPORTATION

- Can be easily refilled at petrol stations.
- Profiled bottom for easy loading.
- Safe and secure to transport.



CONSTRUCTION

- Easy refueling anywhere.



AGRICULTURE

- Optimized for the agriculture industry.

The exact hues of the colours presented in the flyers may differ, depending on the quality of print.
Product specifications may be slightly modified. To obtain an up-to-date equipment specification, contact the office or the nearest distributor.

Distributor:

